



Features:

- Primary tank is built to ULC S601-93. Containment is 110% and built to ULC S653-94.
- Normal and emergency venting. Fill/spill box c/w overfill protection.
- Positive containment monitoring without the concern of faulty or unreliable vacuum gauges
- Durable coatings to protect your investment.

Options:

- Fuel transfer pumps (12v or 115v) with a complete range of sizes and accessories.
- Pump platforms for end dispensing. Low/high level alarm switches.
- Additional top fittings and suction tubes for genset applications.



primary tank						
MODEL	LITRES	I. GALLONS	"A"	"B"	DIA. "C"	WT. LBS
DCS-900	810	180	50"	38"	38"	700
DCS-1350	1240	275	74"	38"	38"	900
DCS-2250	2140	470	74"	50"	50"	1250
DCS-4500	4220	925	145"	50"	50"	2100
DCS-9000	8620	1890	145"	72"	72"	4500
DCS-14000	13200	2894	218"	72"	72"	7000

Sizes are approximate. Actual capacities are within 10% excluding overfill protection.

22424 Fraser Hwy.
 Langley, B.C. V2Z 2T8
 (604) 534-8585 1-800-663-4804
 Fax (604) 534-5814

www.tidy tanks.com

"Tidy Tanks" and "Tanks A Million" are registered trademarks.

